

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 April 2002 (18.04.2002)

PCT

(10) International Publication Number
WO 02/31435 A1

(51) International Patent Classification⁷: **G01B 11/02**,
11/14, 21/16, G01M 17/00, G01L 5/00, G01P 7/00, 15/14

(21) International Application Number: PCT/US01/42652

(22) International Filing Date: 10 October 2001 (10.10.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/239,554 10 October 2000 (10.10.2000) US

(71) Applicant (for all designated States except US): **INTIER
AUTOMOTIVE, INC.** [CA/CA]; 337 Magna Drive, Au-
rora, Ontario L4G 7K1 (CA).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **GABINIEWICZ,
Joseph, V.** [CA/US]; 43757 Parkgrove, Northville, MI
48167 (US). **BRAEUNER, Guenther** [CA/US]; 32240
Craftsbury Road, Farmington Hills, MI 48334 (US).

(74) Agents: **ASHER, Robin, W. et al.**; Clark Hill PLC, Suite
3500, 500 Woodward Avenue, Detroit, MI 48226 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK,
SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, ZA,
ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: CLOSURE MEASURING SYSTEM



(57) Abstract: A closure measuring system for measuring operable specifications of a door panel of an automotive vehicle. The closure measuring system includes a data sensing device adapted to be removably attached to the door panel on the vehicle for sensing and measuring a plurality of operable specifications of the door panel; such as the velocity, energy to move the door and closed door flushness. A control panel is provided for calculating and displaying the sensed and measured operable specifications from the data sensing device and comparing the sensed and measured operable specifications to predetermined design specifications of the door panel. A data acquisition chassis is electrically coupled between the data sensing device and the control panel for storing and transmitting the operable specifications between the data sensing device and the control panel.

BE AVAILABLE COPY

WO 02/31435 A1

CLOSURE MEASURING SYSTEM

BACKGROUND OF THE INVENTION

5 1. Field of Invention

The present invention relates to a closure measuring system, and more particularly, to a closure measuring system for measuring the tolerances and efforts for closing a movable member of an automotive vehicle.

10 2. Background of Invention

Automotive vehicles are equipped with numerous movable components. Such movable components are design with particular tolerances and desired efforts for function and fit. For example, a door of an automotive vehicle is typically pivotally coupled to the body of the vehicle for pivotal movement between an open position providing access
15 through a door opening in the vehicle and a closed position closing the door opening. The door is designed to meet certain predetermined efforts or forces required by the operator to pivot the door between the open and closed positions. Additionally, the door is designed to meet certain predetermined tolerances or alignment requirements with the body of the vehicle when in the closed position.

20 Traditionally, these efforts and tolerance have been manually measured by the designer, engineer or manufacturer without the aid and benefit of a computerized feedback type system for providing fast and accurate measurements.

Therefore, it is desirable to provide a closure measuring system for automatically measuring the efforts, tolerances and other desired design specifications of the movable
25 member of the vehicle.

SUMMARY OF THE INVENTION

The present invention includes a closure measuring system for measuring operable specifications of a movable member of an automotive vehicle. The closure measuring
30 system includes a data sensing device adapted to be removably attached to the movable member on the vehicle for sensing and measuring at least one of a plurality of operable

specifications of the movable member, a control panel for calculating and displaying the sensed and measured operable specifications from the data sensing device and comparing the sensed and measured operable specifications to predetermined design specifications of the member, and a data acquisition chassis coupled between the data sensing device and the control panel for storing and transmitting the operable specifications between the data sensing device and the control panel.

BRIEF DESCRIPTION OF THE DRAWINGS

Advantages of the present invention will be readily appreciated as the same becomes better understood by reference to the following detailed description when considered in connection with the accompanying drawings wherein:

Figure 1 is a schematic perspective view of the closure measuring system according to the present invention; and

Figure 2 is a schematic top view of the closure measuring system..

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Figure 1, a closure measuring system is generally shown at 10 for measuring operable specifications of a movable member of a vehicle during operation through a predetermined range of movement. By way of example, an automotive vehicle is generally shown at 12 including a body portion 14 forming a door opening 16 and a door panel 18 pivotally coupled to the body portion 14 by a hinge mechanism 20 for pivotal movement between an open position providing access into the vehicle 12 through the door opening 16 and a closed position covering the door opening 16 and aligned with the body portion 14. More specifically, the door opening 16 is defined by a circumferential peripheral rim portion 22 of the body portion 14. The door panel 18 similarly includes an outer rim portion 24 which is designed to align flush, or in a single plane, with the rim portion 22 and body portion 14 when the door panel 18 is in the closed position. The distance between the rim portion 22 and the rim portion 24 as well as the alignment therebetween is referred to as the door closed flushness specification and has a predetermined design specification or criteria. It should be appreciated that the movable member may include the door panel 18 or may be any movable member attached to the

vehicle and movable between one or more positions, i.e., a hood, truck, door handle, latch, sunroof, etc.

The closure measuring system 10 includes a data sensing device 26 removably attachable to the movable member, or door panel 18, by an attachment member for sensing
5 and measuring at least one of a plurality of operable specifications of the door panel 18.

The attachment member removably attaches the data sensing device to the door panel at a predetermined position, immediately adjacent the rim portion 24 of the door panel 18, and maintains the positions while the door panel 18 is moved through a predetermined range of movement, i.e. the open and closed positions. The data sensing device 26 in the preferred
10 embodiment shown in Figures 1 and 2 is removably attached to the door panel 18 by a pair of vacuum cups 28. However, it should be appreciated that the data sensing device 26 may be removably attached to the movable member by any suitable attachment member, such as adhesive, magnets, fasteners, or the like.

The operable specifications sensed and measured by the data sensing device 26
15 include the door closing velocity, the door closed flushness, the door latched position, and the energy or force required to close the door. Specifically, the data sensing device 26 acquires the door velocity throughout full door swing between the open and closed positions, the force input required to swing or pivot the door panel 18 and the door closed position (or flushness). Referring to Figures 1 and 2, the data sensing device 26 includes a
20 measuring device such as a gyroscope and loadcell 30 for sensing, measuring and generating electrical signals indicative of the velocity, acceleration and force on the door panel 18 during pivotal movement between the open and closed positions. The data sensing device 26 may also, or alternatively, include an accelerometer for sensing, measuring and calculating the velocity, acceleration and force on the door panel 18.

25 The data sensing device 26 further includes displacement device such as a laser displacement sensor 32 positioned adjacent the door opening rim portion 22 for sensing, measuring, and generating signals indicative of the distance travelled by the door 18 and the door closed flushness between the door panel 18 and the door opening 16. That is, as the door panel 18 is pivoted between the open and closed positions, the laser displacement
30 sensor 32 senses and measures the distance between the rim portion 24 of the door panel 18 and the rim portion 22 of the door opening 16.

Referring again to Figure 1, the closure measuring system 10 further includes a control panel 34 for calculating and displaying the sensed and measured operable specifications from the data sensing device 26 and comparing the sensed and measured operable specifications to predetermined design specifications of the door panel 18. That is, the door panel 18, or any movable member, is designed with predetermined design specifications, such as the force required to pivot the door panel 18 between the open and closed position and the door closed flushness. The control panel 24, which is a software control PC, calculates and displays the sensed and measured operable specifications from the data sensing device 26 and compares them to the predetermined design specifications to display such specifications as velocity in engineering units and a pass/fail indicator, door flushness and a pass/fail indicator, closing energy and a pass/fail indicator, and door latched position. The specifications are also downloadable from the control panel 34.

The closure measuring system 10 further includes a data acquisition chassis 36 coupled between the data sensing device 26 and the control panel 34 for storing and transmitting the operable specifications between the data sensing device 26 and the control panel 34. The data acquisition chassis 36 is electrically coupled to the data sensing device 26 by an input line 38 and then electrically coupled to the control panel 34 by an output line 40.

In operation, the control panel 34 is preprogrammed with software to include the predetermined design specification of the movable member, or door panel 18. The design specifications may include door closed flushness, velocity, and energy required to move the door panel 18. The data sensing device 26 is attached to the door panel 18 by the vacuum cups 28 adjacent the rim portion 24 of the door panel 18 such that the laser displacement sensor 32 is aligned with and adjacent the rim portion 22 of the door opening 16 formed by the body portion 14. The data acquisition chassis 36 is electrically connected between the data sensing device 26 and the control panel 34 by the input 38 and output 40 lines and the system 10 is powered on. As the door panel 18 is pivoted about the hinge mechanism 20 between the open and closed position, the data sensing device 26 senses and measures the operable specification including the velocity of the door panel 18, the energy or force required to pivot the door panel 18 and the door closed flushness between the rim portion 24 of the door panel 18 and the rim portion 22 of the door opening 16. These operable

specifications are transmitted to the data acquisition chassis 36 and control panel 34 by way of electrical signals for display as well as for comparison with the predetermined design specifications. If the operable and measured specifications are within a predetermined plus/minus range of the design specifications, a pass indicator is displayed on the control
5 panel 34. If not, a fail indicator is displayed and the door panel 18 must be adjusted until within acceptable specifications.

The invention has been described in an illustrative manner, and it is to be understood that the terminology, which has been used, is intended to be in the nature of words of description rather than of limitation.

10 Many modifications and variations of the present invention are possible in light of the above teachings. It is, therefore, to be understood that within the scope of the appended claims, the invention may be practised other than as specifically described.

What is claimed is:

1. A closure measuring system for measuring operable specifications of a movable member of an automotive vehicle comprising:
 - a data sensing device adapted to be removably attached to the movable member of
 - 5 the vehicle for sensing and measuring at least one of a plurality of operable specifications of the movable member;
 - a control panel for calculating and displaying said sensed and measured operable specifications from said data sensing device and comparing said sensed and measured operable specifications to predetermined design specifications of the movable member; and
 - 10 a data acquisition chassis electrically coupled between said data sensing device and said control panel for storing and transmitting said operable specifications between said data sensing device and said control panel.
2. A closure measuring system as set forth in claim 1 further including an
 - 15 attachment member for removably attaching said data sensing device to the movable member at a predetermined position and maintain said position while the movable member is operated through a predetermined range of movement.
3. A closure measuring system as set forth in claim 2 wherein said data sensing
 - 20 device includes a measuring device for generating signals indicative of the force applied to the movable member during said predetermined range of movement.
4. A closure measuring system as set forth in claim 3 wherein said data sensing
 - 25 device includes a displacement device for generating signals indicative of the distance travelled by the movable member through said predetermined range of movement.
5. A closure measuring system as set forth in claim 4 wherein said displacement
 - 30 device includes a laser displacement sensor for sensing and measuring the distance travelled by the movable member through said predetermined range of movement and the distance between the movable member and the vehicle.

6. A closure measuring system as set forth in claim 5 wherein said measuring device includes a gyroscope and loadcell for sensing and measuring the velocity, acceleration and force of the movable member operated through said predetermined range of movement.

5

7. A closure measuring system as set forth in claim 5 wherein said measuring device includes an accelerometer for sensing, measuring, and calculating the velocity, acceleration and force of the movable member operated through said predetermined range of movement.

10

8. A closure measuring system as set forth in claim 6 wherein said attachment member includes at least one vacuum cup mounted to said data sensing device for removably securing said data sensing device to the movable member.

15

9. A method of measuring operable specifications of force and distance travelled of a movable member of an automotive vehicle comprising the steps of:

removably attaching a data sensing device in a predetermined position to said movable member;

moving said movable member through a predetermined range of movement relative to said vehicle between an open position and a closed position;

sensing and measuring the force applied to said movable member travelling through said predetermined range of movement;

sensing and measuring the distance travelled by said movable member through said predetermined range of movement;

transmitting electrical signals indicative of said measured force and distance to a data acquisition chassis;

transmitting electrical signals from said data acquisition chassis to a control panel;

calculating and displaying said sensed and measured operable specifications and comparing to predetermined design specifications of said movable member.

30

10. A method as set forth in claim 9 further including sensing and measuring the

velocity of the movable member travelling through said predetermined range of movement.



11. A method as set forth in claim 10 further including sensing and measuring the acceleration of the movable member travelling through said predetermined range of
5 movement.

12. A method as set forth in claim 11 further including measuring the distance between the movable member and the vehicle and comparing said distance to a predetermined design specification of said distance.

10

13. A method as set forth in claim 12 further including comparing said measuring force, velocity and acceleration of said movable member to said predetermined design specifications of said movable member.

15 14. A method as set forth in claim 13 further including displaying a signal from said control panel indicative of whether the sensed and measured operable specification are within a predetermined range of said predetermined design specifications of said movable member.



INTERNATIONAL SEARCH REPORT

In Application No
PC1/US 01/42652

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 G01B11/02 G01B11/14 G01B21/16 G01M17/00 G01L5/00
G01P7/00 G01P15/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 G01B G01M G01L G01P

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 198 60 168 A (TASSAKOS LAMBIS) 20 July 2000 (2000-07-20) column 3, line 58 -column 4, line 56; figure 1	1-3,9-11
Y		4-8, 12-14
Y	WO 00 40940 A (MERITOR LIGHT VEHICLE SYS LTD ;FAUVEAU AXEL (GB); FISHER SIDNEY ED) 13 July 2000 (2000-07-13) page 22; claims 1,2,13-15; figures 5,7	4-8, 12-14
A	WO 98 47018 A (LASER TECHNOLOGY INC) 22 October 1998 (1998-10-22) abstract; figure 1 --- -/--	5

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *G* document member of the same patent family

Date of the actual completion of the international search

21 January 2002

Date of mailing of the international search report

30/01/2002

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Vorropoulos, G

INTERNATIONAL SEARCH REPORT

Int. Application No
PCT/US 01/42652

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>PATENT ABSTRACTS OF JAPAN vol. 1996, no. 09, 30 September 1996 (1996-09-30) & JP 08 114439 A (NIPPONDENSO CO LTD), 7 May 1996 (1996-05-07) abstract</p>	6

INTERNATIONAL SEARCH REPORT

 Inte Application No
 PCI/US 01/42652

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
DE 19860168	A	20-07-2000	DE	19860168 A1	20-07-2000
WO 0040940	A	13-07-2000	AU	1884100 A	24-07-2000
			AU	1884200 A	24-07-2000
			WO	0040940 A1	13-07-2000
			WO	0041155 A1	13-07-2000
WO 9847018	A	22-10-1998	US	5806020 A	08-09-1998
			AU	729605 B2	08-02-2001
			AU	7128898 A	11-11-1998
			EP	0975988 A1	02-02-2000
			WO	9847018 A1	22-10-1998
JP 08114439	A	07-05-1996	NONE		

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.